

DIRECT DRIVEN LUBRICATED COMPRESSORS


D 210/8/24




- Lubricated standard compressor extremely versatile thanks to its 2 Hp power.
- Powerful and practical for all crafts, even those most demanding.
- Simple controls make it easy to use.
- Rubber grip handle and wheels for easy transport.



D 210/8/50



Same characteristics as D 210/8/24 but with a 50-litre tank for a larger air reserve.



Name	Code	Pump	Tank L	Power Hp/kW	Cylinder n°	Max Press. bar/PSI	Lubricated	RPM	Air displacement l/min./CFM	Voltage Frequency Volt/Hz	Gross weight kg/lbs	Box dimensions WxDxH	Cijena MPC
D 210/8/24	FCCE404STN005	FC2	24	2/1,5	1	8/116	SI	2850	222/7,8	230/50	24/52,9	580x255x580	1.229,00kn
D 210/8/50	FCDV404STN006	FC2	50	2/1,5	1	8/116	SI	2850	222/7,8	230/50	36/79,3	770x330x650	1.489,00 kn


DIRECT DRIVEN LUBRICATED COMPRESSORS

New lubricated compressors with 2 Hp and 2,5 Hp pump ideal for all hobby activities and enriched with technical solutions that simplify use.



Sturdy wheels ensure greater stability and handling.

D 210/8/24S



Gauges on the compressor for easier reading.



Large fully tilted handle for easy transport.

D 250/10/50S



NEW

Name	Code	Stanley code	Pump	Tank L	Power Hp/kW	Cylinder n°	Max Press. bar/PSI	Lubricated	RPM	Air displacement l/min./CFM	Voltage Frequency Volt/Hz	Gross weight kg/lbs	Box dimensions WxDxH	Cijena MPC
D 210/8/24S	FCCC404STN640	SXCM0051E	FC2	24	2/1,5	1	8/116	SI	2850	222/7,8	230/50	26/57,3	580x255x580	1.299,00 kn
D 250/10/24S	FCCC4G4STN653	SXCM0053E	FC2,5	24	2,5/1,8	1	10/145	SI	2850	240/8,5	230/50	26,5/58,4	580x255x580	1.399,00kn
D 210/8/50S	FCDV404STN641	SXCM0052E	FC2	50	2/1,5	1	8/116	SI	2850	222/7,8	230/50	33/72,7	770x330x650	1.559,00 kn
D 250/10/50S	FCDV4G4STN654	SXCM0054E	FC2,5	50	2,5/1,8	1	10/145	SI	2850	240/8,5	230/50	33,5/73,8	770x330x650	1.689,00 kn

DIRECT DRIVEN LUBRICATED COMPRESSORS

D 261/10/24




- Sturdy, compact and 2.5 Hp makes it the perfect tool for the most demanding hobby worker.
- Comfortable rubber grip handle and large wheels for easy transport.
- Double fixed front foot for enhanced stability during use.
- Large gauges on the compressor for easier reading, pressure reducer knob with innovative "snap" adjustment mechanism.



D 261/10/50



Same characteristics as D 261/10/24 but with a 50-litre tank for a larger air reserve.



Name	Code	Pump	Tank	Power	Cylinder	Max Press.	Lubricated	RPM	Air displacement	Voltage Frequency	Gross weight	Box dimensions	Cijena MPC
			L	Hp/kW	n°	bar/PSI			l/min./CFM	Volt/Hz	kg/lbs	WxDxH	
D 261/10/24	FCCC4G4STN593	FC2,5	24	2,5/1,8	1	10/145	SI	2850	250/8,8	230/50	30/66,1	580x255x580	1.899,00 kn
D 261/10/50	FCDV4G4STN594	FC2,5	50	2,5/1,8	1	10/145	SI	2850	250/8,8	230/50	37,7/83,1	770x330x650	2.259,00 kn